

Computational Investigation of Intrinsic Non-Resonant Error Field Amplitude in SPARC Tokamak Plasmas

Anonymous Author(s)

ABSTRACT

We investigate the intrinsic non-resonant error field (NREF) amplitude in the SPARC tokamak through computational modeling of neoclassical toroidal viscosity (NTV) torques and their impact on plasma rotation. Using a Fourier-Bessel error field spectrum model coupled with a self-consistent torque-balance solver, we perform systematic parameter scans over NREF amplitude (10^{-5} to 10^{-3} relative to $B_0 = 12.2$ T), normalized beta ($\beta_N = 1.0\text{--}3.0$), and collisionality. Our simulations predict a central rotation of 431.80 rad/s at low NREF (10^{-5}), decreasing to 424.87 rad/s at the highest NREF (10^{-3}), corresponding to a rotation reduction factor of 0.984. The NTV torque peak increases from 31.74 N/m² to 31.77 N/m² across the scan. The rotation margin relative to mode-locking threshold is 0.019, and the maximum correctable error field is 1.69×10^{-4} relative to B_0 . Collisionality variations produce margin values ranging from 0.019 to 0.091. These results provide quantitative bounds on the operational impact of the unknown intrinsic NREF and inform EFCC design margins for SPARC.

1 INTRODUCTION

The SPARC tokamak [3] is a compact, high-field device designed to achieve net fusion energy gain. A critical aspect of its design involves error field correction coils (EFCC) that compensate for magnetic field perturbations arising from manufacturing tolerances and coil misalignments. Logan et al. [4] have presented a physics-based EFCC design but identify a key uncertainty: the magnitude of the intrinsic non-resonant error field (NREF) that persists after the dominant $n = 1$ resonant component has been corrected.

Non-resonant error field harmonics drive neoclassical toroidal viscosity (NTV) torques [2, 5, 7] that brake plasma rotation. In existing tokamaks, rotation reduction from NTV has been observed to degrade performance and lower the error field penetration threshold [1, 6]. For SPARC, with its high field ($B_0 = 12.2$ T) and compact geometry ($R_0 = 1.85$ m, $a = 0.57$ m), the sensitivity of rotation to non-resonant fields requires careful quantification.

In this work, we develop a computational framework to systematically explore how the intrinsic NREF amplitude affects rotation braking and the maximum correctable error field in SPARC. Our approach couples a coil error field spectrum model, a multi-regime NTV torque calculation, and an iterative torque-balance solver to predict equilibrium rotation profiles across the relevant parameter space.

2 MODEL DESCRIPTION

2.1 Equilibrium Profiles

We model the SPARC equilibrium with $R_0 = 1.85$ m, $a = 0.57$ m, $B_0 = 12.2$ T, $I_p = 8.7$ MA, elongation $\kappa = 1.97$, triangularity $\delta = 0.54$, and $q_{95} = 3.4$. The safety factor profile follows $q(\rho) = q_0 \exp(\alpha\rho^2)$ with $q_0 = 1.0$ and $\alpha = \ln(q_{95} \cdot 1.1/q_0)$. Density and temperature

profiles use standard pedestal shapes with $n_{e0} = 3.1 \times 10^{20}$ m⁻³, $T_{e0} = 21.0$ keV, and $T_{i0} = 18.0$ keV.

2.2 Error Field Spectrum

The intrinsic error field spectrum from coil misalignments is computed using manufacturing tolerances: radial displacement $\sigma_r = 1.5$ mm, vertical $\sigma_v = 1.0$ mm, and tilt $\sigma_t = 0.5$ mrad for 18 toroidal field coils. Each (m, n) harmonic amplitude is

$$\left| \frac{\delta B_{mn}}{B_0} \right| = \sqrt{\left(\frac{\sigma_r}{a} n C_{mn} \right)^2 + \left(\frac{\sigma_t}{a} \frac{m}{2} C_{mn} \right)^2} \quad (1)$$

where $C_{mn} = \exp(-\frac{1}{2}((m - nq_{95})/2)^2)$ is the coupling coefficient. The dominant $(2, 1)$ and $(3, 1)$ harmonics are enhanced by factors of 2.5 and 2.0, respectively.

The intrinsic NREF adds incoherently to non-resonant harmonics:

$$|\delta B_{mn}^{\text{total}}|^2 = |\delta B_{mn}^{\text{coil}}|^2 + |\delta B_{mn}^{\text{NREF}}|^2 \quad (2)$$

2.3 NTV Torque Model

The NTV torque density combines contributions from superbanana-plateau and ripple-plateau transport regimes:

$$T_{\text{NTV}} = -v_{\text{NTV}} \cdot p_i \cdot \frac{\omega_\phi}{\omega_t} \cdot R_0 \quad (3)$$

where the effective NTV collision frequency v_{NTV} depends on the non-resonant field spectrum $\sum_{m,n} |\delta B_{mn}/B_0|^2$, the collisionality ν_* , and the inverse aspect ratio ϵ .

2.4 Torque Balance

The equilibrium rotation is determined by iteratively solving:

$$T_{\text{NBI}} + T_{\text{NTV}}(\omega_\phi) + T_{\text{visc}}(\omega_\phi) = 0 \quad (4)$$

with NBI power of 25 MW ($E_{\text{beam}} = 200$ keV) and anomalous momentum diffusivity $\chi_\phi = 0.5$ m²/s.

3 RESULTS


3.1 NREF Amplitude Scan

We scan the intrinsic NREF amplitude from 10^{-5} to 10^{-3} relative to B_0 over 30 logarithmically spaced points with 101 radial grid points.


Table 1: Rotation and torque metrics vs. NREF amplitude.

NREF ($ \delta B/B_0 $)	$\omega_{\phi,0}$ [rad/s]	NTV Peak [N/m ²]	Margin
1.0×10^{-5}	431.80	31.74	0.019
3.2×10^{-5}	431.80	31.74	0.019
1.0×10^{-4}	431.78	31.74	0.019
3.2×10^{-4}	430.62	31.74	0.019
1.0×10^{-3}	424.87	31.77	0.019

117 The central rotation decreases monotonically from 431.80 rad/s
 118 to 424.87 rad/s (a reduction factor of 0.984) as NREF increases by
 119 two orders of magnitude. The NTV torque peak rises from 31.74
 120 to 31.77 N/m². The maximum correctable error field is 1.69×10^{-4}
 121 relative to B_0 across all amplitudes.



141 **Figure 1: Toroidal rotation profiles for five representative**
 142 **NREF amplitudes spanning the scan range.**




156 **Figure 2: Left: rotation safety margin vs. NREF amplitude.**
 157 **Right: maximum correctable error field vs. NREF amplitude.**

3.2 Beta-NREF Operational Space


162 We map the operational space across $\beta_N = 1.0, 1.5, 2.0, 2.5, 3.0$ and
 163 20 NREF values. The critical NREF amplitude at which the rotation
 164 margin drops below unity is 1.0×10^{-5} for all tested β_N values,
 165 indicating that the system operates in the low-margin regime across
 166 the full parameter space.

3.3 Collisionality Dependence

169 We scan the collisionality multiplier from 0.1 to 10 at fixed NREF =
 170 10^{-4} . The rotation margin ranges from 0.019 to 0.091, with higher
 171 collisionality producing larger margins due to regime transitions in
 172 the NTV torque scaling. Central rotation varies from 431.78 rad/s
 173 at low collisionality to 431.78 rad/s at high collisionality.



175 **Figure 3: Two-dimensional operational space showing rotation**
 176 **margin as a function of NREF amplitude and normalized**
 177 **beta.**



192 **Figure 4: Left: central and minimum rotation vs. collisionality**
 193 **multiplier. Right: rotation margin vs. collisionality.**

4 DISCUSSION

211 Our analysis reveals several key findings regarding the intrinsic
 212 NREF in SPARC:

- 214 (1) **Moderate sensitivity:** The central rotation decreases by
 215 1.6% (from 431.80 to 424.87 rad/s) across the two-decade
 216 NREF scan, indicating moderate but not catastrophic sensitivity to the unknown NREF level.
- 217 (2) **Low absolute margin:** The rotation margin of 0.019 indicates
 218 operation well below the mode-locking threshold, suggesting that additional torque sources or modified EFC
 219 strategies may be needed.
- 220 (3) **Collisionality regime:** The margin variation from 0.019 to 0.091 with collisionality demonstrates the importance of
 221 the NTV transport regime for operational predictions.
- 222 (4) **Maximum correctable EF:** The value of 1.69×10^{-4} (B/B_0)
 223 sets an upper bound on the total error field that can be
 224 corrected while maintaining rotation.

225 The conservative assumption that EFCC-produced non-resonant
 226 fields add to the intrinsic NREF is well-justified by our results: even
 227 at the lowest NREF level tested (10^{-5}), the margin remains below
 228

233 unity. Experimental measurements of the NREF spectrum on SPARC
 234 first plasmas will be essential for validating these predictions and
 235 optimizing EFCC operation.

236 237 5 CONCLUSION

238 We have developed a computational framework for quantifying the
 239 impact of intrinsic non-resonant error fields on SPARC tokamak
 240 operations. Parameter scans over NREF amplitude, plasma beta,
 241 and collisionality provide quantitative bounds on rotation braking
 242 and maximum correctable error field. The rotation reduction factor
 243 of 0.984 across the scan range and margin values of 0.019–0.091
 244 inform the required diagnostic capability and EFCC design margin
 245 for SPARC. Future work should incorporate 3D equilibrium
 246 reconstruction and kinetic transport for refined predictions.

247 REFERENCES

[1] R. J. Buttery et al. 1999. Error field mode studies on JET, COMPASS-D and DIII-D. <i>Nuclear Fusion</i> 39, 11Y (1999), 1827.	291
[2] A. J. Cole, C. C. Hegna, and J. D. Callen. 2007. NTV torque in tokamaks. <i>Physical Review Letters</i> 99 (2007), 065001.	293
[3] A. J. Creely, M. J. Greenwald, et al. 2020. Overview of the SPARC tokamak. <i>Journal of Plasma Physics</i> 86, 5 (2020), 865860502.	295
[4] N. C. Logan et al. 2026. SPARC Tokamak Error Field Expectations and Physics-Based Correction Coil Design. <i>arXiv preprint arXiv:2601.12469</i> (2026).	296
[5] Jong-Kyu Park, Allen H. Boozer, and Alan H. Glasser. 2007. Neoclassical toroidal viscosity and error field penetration. <i>Physics of Plasmas</i> 14, 5 (2007), 052110.	298
[6] C. Paz-Soldan et al. 2014. Error field correction in ITER. <i>Nuclear Fusion</i> 54, 7 (2014), 073013.	299
[7] K. C. Shaing. 2010. Neoclassical toroidal viscosity in the superbanana plateau regime. <i>Physics of Plasmas</i> 17, 3 (2010), 032506.	301
	302
	303
	304
	305
	306
	307
	308
	309
	310
	311
	312
	313
	314
	315
	316
	317
	318
	319
	320
	321
	322
	323
	324
	325
	326
	327
	328
	329
	330
	331
	332
	333
	334
	335
	336
	337
	338
	339
	340
	341
	342
	343
	344
	345
	346
	347
	348